PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶:
B01F 3/00, A61K 7/00, 9/10, B01D 9/02

(11) International Publication Number:

WO 99/59709

(43) International Publication Date:

25 November 1999 (25.11.99)

(21) International Application Number:

PCT/GB99/01432

A1

(22) International Filing Date:

7 May 1999 (07.05.99)

(30) Priority Data:

9810859.0

20 May 1998 (20.05.98)

GB

(71) Applicant (for all designated States except US): ZENECA LIMITED [GB/GB]; 15 Stanhope Gate, London W1Y 6LN (GB).

(72) Inventors; and

- (75) Inventors/Applicants (for US only): WOOD, William, Malcolm, Logan [GB/GB]; Huddersfield Works, Leeds Road, P.O. Box A38, Huddersfield HD2 1FF (GB). DAWSON, Stephen [GB/GB]; Huddersfield Works, Leeds Road, P.O. Box A38, Huddersfield HD2 1FF (GB). GEORGE, Neil [GB/GB]; Huddersfield Works, Leeds Road, P.O. Box A38, Huddersfield HD2 1FF (GB).
- (74) Agents: HOUGHTON, Malcolm, John et al.; Zeneca Agrochemicals, Intellectual Property Dept., Jealott's Hill Research Station, P.O. Box 3538, Bracknell RG42 6YA (GB).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: PROCESS FOR PREPARING A CRYSTAL SUSPENSION

(57) Abstract

A process for preparing a crystal suspension of an organic compound which has a Δ H/RT value in the range of from 1 to 10, the process comprising dispersing a melt of the organic compound in a liquid dispersion medium to form an emulsion, cooling the emulsion below the melting point of the organic compound and subjecting the emulsion to ultrasonic vibration.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	ТJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Treland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	$\mathbf{z}\mathbf{w}$	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

WO 99/59709 PCT/GB99/01432

PROCESS FOR PREPARING A CRYSTAL SUSPENSION

This invention relates to a crystallisation process and, in particular, to a process for producing a crystalline suspension of an organic compound in a liquid medium.

In many industries, especially in the agrochemical, pharmaceutical and biocide industries, active ingredients are often supplied in the form of suspension concentrates. These comprise a largely insoluble, particulate active ingredient suspended in a liquid medium, usually an aqueous medium. They are commonly prepared by ball or bead milling a millbase consisting of the active ingredient, liquid medium and one or more dispersing agents, and then formulated with additives and a volume-adjusting amount of the liquid medium. Additives may include, for example, antisettling or suspension agents, preservatives, antifoams, antifreezes and biological adjuvants.

It is important to industry to be able to provide fluid, storage stable concentrates without the need for stirred storage vessels or the use of thickeners to maintain the solid particles in suspension. A key factor in obtaining a physically stable product is the particle size of the suspended solid. Normally, the smaller the particle size, the more stable is the suspension.

Milling is a common technique for reducing the particle size of a suspended solid, but may not always produce the best results, and, because it generates considerable heat, may not always be appropriate, for example, where the active ingredient is a low melting solid.

An alternative technique is to crystallise the solid from an emulsion of the melted solid, or a solution of it, in the liquid medium. For example, it is known from EP-A-0221465 to prepare suspensions by dispersing a melt above its solidification temperature in an aqueous phase and allowing the melt to solidify by cooling it below its crystallisation temperature. It is also known from DE-A-2551841 and DE-A-2900268 that a melt can be dispersed in an aqueous phase having a temperature below the solidification temperature of the melt. Dispersions of this type are produced using high speed stirrers or rotor-stator machines. The disadvantage of these processes is that they tend to give only coarse dispersions with short shelf lives, although finer dispersions may be obtained if, as described in EP-A-0399266, the initial emulsion is subjected to an additional homogenisation step.

In these emulsions, the melt is suspended in the aqueous phase in the form of droplets. If the droplets crystallise rapidly, the crystal size distribution will be the same as

30

5

10

15

20

25

10

15

20

25

30

the original droplet size within the emulsion. Therefore, in theory, it should be possible to generate finer and more stable dispersions by reducing the droplet size. However, as the droplet size decreases, crystallisation becomes slower. Furthermore, the solubility of the droplet in the continuous phase increases with decreasing droplet size, due to higher pressures within the droplet. The effect of this is that the continuous phase concentration can rise to a level where it becomes supersaturated relative to the crystalline form, with the result that nucleation and crystal growth occurs in the continuous phase. As nucleation rates tend to be slow in the continuous phase, large crystals are generated which bear no resemblance to the original droplets. This is clearly undesirable if fine dispersions are to be obtained.

The use of ultrasound for crystallising melts and solutions is well known. For example, a process for the crystallisation of adipic acid from aqueous solution is known from US-A-5471001. It is also known to use ultrasonics for preparing emulsions and fine droplet dispersions (see, for example, WO-A-94/20072). It has now been found that ultrasound can be used to generate finer particle size, more stable dispersions from emulsions.

Thus, according to the present invention there is provided a process for preparing a crystalline suspension of an organic compound which has a $\Delta H/RT$ value in the range of from 1 to 10, the process comprising dispersing a melt of the organic compound in a liquid dispersion medium to form an emulsion, cooling the emulsion below the melting point of the organic compound and subjecting the emulsion to ultrasonic vibration.

The value ΔH/RT is a well understood expression which means the enthalpy (heat) of fusion of a compound (ΔH in kJmol⁻¹) at the normal melting point of the compound divided by the molar gas constant (R, where R is 8.31451 Jmol⁻¹K⁻¹) and the melting point of the compound measured on the absolute or Kelvin scale (in °K). Thus, for example, the ΔH/RT value of octadecane, which has a melting point of 28.2 °C and a heat of fusion of 61.39kJmol⁻¹ (see the *CRC Handbook of Chemistry and Physics*, [1996-1997], 77th Edition, 6-138) is calculated as follows:

 $61.39/8.31451x10^{-3}x(28.2+273.16) = 24.5$

The heat of fusion of a compound (ΔH) may be measured by differential scanning calorimetry. A suitable method is described by McNaughton, J.L. and Mortimer, C.T. in IRS: Physical Chemistry Series 2, Butterworth, London 1975, Vol 10; subsequently reprinted by Perkin-Elmer Corpn. Norwalk, CT, USA.

10

15

20

25

30

In a preferred aspect of the invention process, the organic compound has a $\Delta H/RT$ value in the range of from 5 to 10.

The invention is of particular interest in the formulation of low melting agrochemicals, especially pesticides such as fungicides, insecticides and herbicides, and low melting pharmaceutical and biocide products as suspension concentrates. It will be evident, however, that the process is equally applicable to the preparation of a crystalline suspension of any other low melting organic compound.

Where the crystalline suspension is to be stored for long periods at ambient temperature, it is desirable that the organic compound has a melting point above 20°C and, preferably, above 30°C. However, the melting point should not be higher than the boiling point of the chosen liquid medium dispersion medium at its operating pressure. This pressure will be as high as it is reasonably practicable or economical to pressurize the apparatus being used. Thus, where the liquid medium is water, as will normally be the case, the organic compound may have a melting point of from 20°C to 200°C, the upper temperature being possible where the apparatus is pressurized to around 10bar. Suitably the organic compound will have a melting point of from 20°C to 120°C for example, from 30°C to 100°C and, typically, from 40°C to 90°C.

The liquid dispersion medium, which may be any suitable liquid, for example, water or an agriculturally acceptable organic solvent that is benign to living tissue, will ideally have a crystallisation point of at least 10°C, suitably 20°C, below the crystallisation point of the organic compound, and a boiling point of at least the same order as the melting point of the organic compound, and preferably at least 5°C above the melting point of the organic compound, for example, from 10°C to 30°C above. Of most interest, however, are those suspensions where the liquid dispersion medium is an aqueous medium and where the emulsion formed is an oil-in-water emulsion.

Conveniently, the organic compound is melted and heated to a temperature slightly above its melting point, for example 5°C to 10°C above, and added to the liquid dispersion medium heated to approximately the same temperature as the melt, ie within 5°C or so. Alternatively, the organic compound may be added to the liquid medium at a temperature above or below the melting point of the organic compound, for example prior to heating to the melt temperature, and the temperature adjusted until the organic compound has melted.

10

15

20

25

Depending on the crystallisation properties of the organic compound, it may also be possible to add the melt to the liquid medium at a temperature below the melting point of the organic compound without further heating.

The concentration of the organic compound in the liquid dispersion medium will be up to 60% w/w, normally from 1% w/w to 60% w/w, for example, from 1% w/w to 20% w/w.

The liquid medium may contain additives, for example one or more dispersing agents, or other additives of the type normally used in the preparation of crystalline suspensions and which are well documented in the literature. The amount of additive used will normally be in the range of from 0.01% w/w to 10% w/w, for example from 0.05% w/w to 5% w/w, and typically from 0.1% w/w to 2% w/w of the total dispersion medium.

The liquid medium containing the melt or solution is vigorously agitated using, for example, a high shear mixer or homogeniser or a combination of these, to generate the desired droplet size of the suspended organic compound. Generally, droplet sizes of less than $10\mu m$ (mean diameter), for example between $1\mu m$ and $10\mu m$ and preferably between $1\mu m$ and $5\mu m$, are required, but the present invention is also applicable to sub-micron droplets.

The emulsion so formed is cooled, preferably as rapidly as possible, to a temperature below the melting point of the organic compound, suitably to a temperature of from 1°C to 80°C, depending on the melting point of the organic compound and the nature of the liquid dispersion medium. For a compound with a melting point of, for instance, 70°C to 80°C and where the liquid dispersion medium is water, the emulsion may be cooled from 30°C to 70°C, for example from 50°C to 60°C, below the melting point of the organic compound. For a compound with a melting point of, for instance, 20°C to 40°C, the emulsion may be cooled from 1°C to 20°C, for example from 3°C to 10°C, below the melting point of the organic compound. After cooling, ultrasonic vibration is applied until crystallisation has progressed to an acceptable degree. This may be done either batch-wise or continously by passing a continuous stream of the emulsion through a vessel in which the ultrasonic vibration is applied. Feeding the emulsions through a continuous sonication device may enhance the droplet nucleation rate thereby generating finer, more stable dispersions.

Any suitable source of ultrasonic vibration may be used. A half-inch diameter (12.7mm) ultrasonic probe operating at 20kHz and a power input of 100watts has been found convenient, but there will be many other commercially available devices equally suitable.

The invention is of particular interest for preparing a crystalline suspensions of low melting organic compounds with a suitable $\Delta H/RT$ value, such as ibuprofen, piperonal, camphene, 3-iodo-2-propynyl butyl carbamate and like compounds.

The invention is illustrated by the following Examples in which *Mowiol* ¹18-88, which is a poly(vinyl alcohol) 88% hydrolysed (molecular weight 18,000), is used as a dispersing agent. The following abbreviations are used throughout:

10

15

20

5 -

g = grammes	%w/w = percent weight by	°C = degrees centigrade
l = litres	weight	hr = hour
rpm = revolutions per	ml = millilitres	ΔH = heat of fusion (kJmol ⁻¹)
minute	mp = melting point	T = temperature in degrees
		Kelvin
R = molar gas constant (8.314)	151 Jmol ⁻¹ k ⁻¹)	w = watt

EXAMPLE 1

Preparation of an aqueous dispersion (1% w/w) of ibuprofen (α -methyl-4-(2-methylpropyl)benzene acetic acid: mp 74°C, Δ H/RT 9.33).

Ibuprofen (10g) and an aqueous solution of *Mowiol* 18-88 (990g, 2% w/w) in a dispersion vessel were heated to 80°C using a water bath to melt the ibuprofen. The molten ibuprofen was dispersed in the surfactant solution using a preheated high shear mixer (ultraturrax, 9500rpm). The mixture was emulsified for five minutes and produced a stable dispersion with a droplet size of no greater than 10μm. The hot emulsion was pumped (peristaltic pump, 6 1hr⁻¹) through a cooled coil to reduce the emulsion temperature to 20°C, then fed directly into a continuous sonication vessel (approximately 30ml sonicated volume) fitted with a high intensity sonic probe (500w). Two samples (50ml each) were collected. The first was untreated and the second was cooled rapidly using ice/water. The flow rate was then reduced to 2 1hr⁻¹ and two samples collected and treated as above.

¹ The name Mowiol is a registered trade mark

15

20

25

30

All four samples showed fine ($<10\mu m$) crystalline needles which formed immediately after sonication. The number of particles in the final dispersion was similar to the number of droplets in the original hot emulsion which indicated nucleation had occurred preferentially in the droplets. There was no effect of flow rate. By contrast, ibuprofen emulsion samples (2% aqueous dispersion) produced in a similar manner, at a fifth of the scale, but which were allowed to cool without sonication, both naturally to room temperature and rapidly using ice/water, contained non-birefringent (i.e. non-crystalline) droplets after 2 hr and then produced large ($100-200\mu m$) twinned crystals when cooled and equilibrated for 18hrs. The crystals appeared to have grown from a continuous phase.

EXAMPLE 2

Preparation of a more concentrated aqueous dispersion (20% w/w) of ibuprofen than in Example 1.

Ibuprofen (40g) and an aqueous solution of *Mowiol* 18-88 (160g, 2% w/w) in a dispersion vessel were heated to 80°C using a water bath to melt the ibuprofen. The molten ibuprofen was dispersed in the surfactant solution using a preheated high shear mixer (ultraturrax, 9500prm). The mixture was emulsified for five minutes and produced a stable dispersion with a droplet size of no greater than 10μm. The hot emulsion was pumped (peristaltic pump, 6 1hr⁻¹) through a cooled coil to reduce the emulsion temperature to 20°C then fed directly into a continuous sonication vessel (approximately 30ml sonicated volume) fitted with a high intensity sonic probe (500w). Two emulsion samples (50ml each) were collected. The first was untreated and the second was cooled rapidly in ice/water. The flow rate was then reduced to 2 1hr⁻¹ and two samples collected and treated as above. Each emulsion was sampled periodically during cooling by mounting a small sample for image analysis by optical microscope as follows.

A small sample of the cooled sonicated emulsion was transferred using a capillary tube to a microscope slide and was protected with a glass cover slip. The slide was viewed using transmitted light or cross-polarised light (Zeiss microscope) and an image recorded on a calibrated micrograph. The micrograph provides information as to the size (μ m), shape and degree of crystallinity of the droplets or crystals.

10

15

20

25

30

All four samples showed fine ($<10\mu m$) crystalline spheres to have been formed immediately after sonication. The number of spheres/particles in the final dispersion was similar to the number of droplets in the original hot emulsion, which indicated nucleation had occurred preferentially in the droplets.

EXAMPLE 3

Preparation of an aqueous dispersion (1% w/w) of piperonal (3,4-(methylenedioxy)benzaldehyde: mp 35.6°C, ΔH/RT 5.00).

An emulsion of piperonal in surfactant solution was prepared as in Example 1 (substituting piperonal for ibuprofen). The droplet size was estimated to be less than $2\mu m$. The hot piperonal emulsion was pumped (peristaltic pump, $6~1hr^{-1}$) through a cooled coil to reduce the emulsion temperature to $20^{\circ}C$, then fed directly into a continuous sonication vessel (approximately 30ml sonicated volume) fitted with a high intensity sonic probe (500w). Two samples were collected. The first was untreated and the second was cooled rapidly in ice/water. The flow rate was then reduced to $2~1hr^{-1}$ and two samples collected and treated as above.

All four samples produced by sonication showed a mixture of rectangular plates (10-30 μ m) and smaller crystalline material (2-5 μ m). There was no evidence of relay crystallisation (see below).

By way of comparison, piperonal emulsion samples were produced in a similar manner, at a fifth of the scale, but were allowed to cool without sonication, both naturally to room temperature and rapidly using ice/water. Each emulsion was sampled periodically during cooling for image analysis by optical microscope (see Example 2).

The sample allowed to cool naturally produced a multitude of long coiled rods which grew rapidly after nucleation had occurred (2hr). The length of these crystals was far larger than the dimensions of the droplet, indicating little droplet nucleation and substantial growth from a continuous phase.

The sample cooled rapidly using ice/water produced large (>100 μ m) highly ordered crystalline structures which grew rapidly by a process known as "relay crystallisation". (In relay crystallisation, fewer droplets nucleate and the dispersion is crystallised predominantly by the transmission of crystallinity (from droplet to droplet) in a front moving away from the

10

15

20

25

30

original event. By contrast, when sonicated, the whole dispersion completely crystallises indicating many more droplet nucleation events.)

EXAMPLE 4

Preparation of a 20% w/w aqueous dispersion of piperonal.

Piperonal (50g) and an aqueous solution of *Mowiol* 18-88 (199g water:1g *Mowiol*) were heated to 50°C using a water bath to melt the piperonal. The molten piperonal was dispersed in the surfactant solution using a preheated high shear mixer (ultra-turrox, 9500 rpm). The mixture was emulsified for five minutes to produce a stable dispersion with a droplet size of no greater than 10μm. Samples of the emulsion were transferred to three small bottles (50ml) and each was cooled to 28°C. One sample, designated (a), was subjected to ultrasonic vibration using a high intensity sonic probe (500w) for 30 seconds. Another sample, designated (b), was sonicated for 0.5 seconds at 10 second intervals over a period of 600 seconds. The third sample, designated (c), was not sonicated (untreated).

Each sample was analysed periodically under an optical microscope by the method described in Example 2. The samples which were subjected to either pulsed or constant high energy sonications produced crystalline dispersions where nucleation had clearly occurred within the droplet and some limited growth had continued beyond the droplet boundary producing crystals resembling the size and number of the original droplet dispersion. The untreated sample exhibited rapid relay crystallisation reflecting lower droplet nucleation and high continuous phase growth - the resulting crystals were larger.

EXAMPLE 5

Preparation of an aqueous 1% w/w dispersion of piperonal.

An emulsion of piperonal in surfactant was prepared as in Example 1 (substituting piperonal for ibuprofen) except in this case only 0.1% *Mowiol* 18-18 was used (10g piperonal; 989g water; 1g *Mowiol*). The hot piperonal emulsion was pumped (peristaltic pump) at 2 lhr⁻¹ through a cooled coil to reduce the emulsion temperature to 28°C then fed directly into a continuous sonication vessel (approximately 30ml sonicated volume) fitted with a high intensity sonic probe (500 watt). The processed emulsion was sampled again and the flow rate increased to 6 lhr⁻¹. The emulsion was sampled after a period of equilibration. Each sample was analysed periodically by the method described in Example 2. Both samples produced crystalline dispersions where nucleation had clearly occurred within the

10

15

20

25

30

droplet and some limited growth had continued beyond the droplet boundary producing crystals resembling the size and number of the original droplet dispersion.

By comparison an untreated, under-cooled sample of emulsion collected in the feed tubes had clearly crystallised by the process of relay crystallisation.

EXAMPLE 6

Preparation of an aqueous dispersion (1% w/w) of (-) camphene ((1S)-2,2-dimethyl-3-methylenebicyclo[2.2.1]heptane: mp 40.5° C, Δ H/RT 1.15).

An emulsion of camphene in surfactant solution was prepared as in Example 1 (substituting camphene for ibuprofen). The hot camphene emulsion was pumped (peristaltic pump) at 6 1hr⁻¹ through a cooled coil, to reduce the emulsion temperature to 20°C, then fed directly into a continuous sonication vessel (approximately 30ml sonicated volume) fitted with a high intensity sonic probe (500w). Two samples were collected. The first was untreated and the second was cooled rapidly in ice/water. The flow rate was then reduced to 2 1hr⁻¹ and two samples collected and treated as above.

All four samples showed nucleation to have occured in the majority of the droplets. In the case of the lower flow rate samples the number of spheres/particles in the final dispersion was similar to the number of droplets in the original hot emulsion which indicated nucleation had occurred prefentially in the droplets.

For the higher flow cases there were some plates (30 μ m) but mainly small needles (2 μ m).

By contrast camphene emulsion samples produced in a similar manner, but which were allowed to cool without sonication, both naturally to room temperature and rapidly using ice/water, showed non-birefringement shapes similar in size to the original dispersion. The edges of the shapes were smooth not faceted.

EXAMPLE 7

Preparation of an aqueous 1% w/w dispersion of camphene.

An emulsion of camphene in surfactant was prepared as in Example 1 (substituting camphene for ibuprofen) except in this case only 0.1% *Mowiol* 18-88 was used (10g camphene; 989g water; 1g *Mowiol*).

The hot emulsion was pumped (peristaltic pump) at 2 lhr⁻¹ through a cooled coil to reduce the emulsion temperature to 20°C then fed directly into a continuous sonication vessel

15

20

25

30

(approximately 30ml sonicated volume) fitted with a high intensity sonic probe (500 watt). The processed emulsion was sampled and the flow rate increased to 6 lhr⁻¹. The emulsion was again sampled after a period of equilibration. Each sample was analysed by the method described in Example 2. The sample taken at the higher flow rate produced amorphous droplets, while the sample taken at the lower flow rate showed crystallisation to have occurred within the droplets. An unsonicated sample of the emulsion remained in the amorphorus state.

EXAMPLE 8

Preparation of an aqueous dispersion (1% w/w) of 3-iodo-2-propynyl butyl carbamate (IPBC: mp 67.5°C, ΔH/RT 9.25).

3-Iodo-2-propynyl butyl carbamate (IPBC: 10g) and an aqueous solution of *Mowiol* 18-88 (970g water: 20g *Mowiol*) were heated to 80°C using a water bath to melt the IPBC. The molten IPBC was dispersed in the surfactant solution using a preheated high shear mixer (ultra-turrex, 9500 rpm). The mixture was emulisfied for five minutes to produce a stable dispersion with a droplet size of no greater than 10μm. The hot emulsion was pumped (peristaltic, 6 1hr⁻¹) through a cooled coil to reduce the emulsion temperature to 20°C then fed directly into a continuous sonication vessel (approximately 30ml sonicated volume) fitted with a high intensity sonic probe (500watt). Two samples were collected, the first was untreated and the second was cooled rapidly in ice/water. The flow rate was reduced to 2 lhr⁻¹ and two samples were treated as above.

When analysed under an optical microscope as described in Example 2, all four sonicated samples showed that fine ($<10\mu m$) crystalline spheres had been formed immediately after sonication. The number of spheres/particles in the final dispersion was similar to the number of droplets in the original hot emulsion which indicated nucleation had occurred preferentially in the droplets. The samples showed no sign of "Ostwäld" ripening (crystal growth) after one week. The change of flow rate resulted in no apparent effect.

For comparative purposes a 1% w/w emulsion of IPBC was prepared in the same way but the hot emulsion was cooled in two batches; the first batch being allowed to cool naturally to room temperature and the second batch being cooled rapidly using a ice/water bath. Each emulsion was sampled periodically during cooling for image analysis as described in Example 2. Both samples produced "fern like" growth with large numbers of

small particles growing in clusters (after 30 minutes cooling). On standing for several days the samples had appeared to have ripened and produced larger ($25x10\mu m$) crystals.

25

CLAIMS

- A process for preparing a crystal suspension of an organic compound which has a
 ΔH/RT value in the range of 1 to 10, the process comprising dispersing a melt of the
 organic compound in a liquid dispersion medium to form an emulsion, cooling the
 emulsion below the melting point of the organic compound and subjecting the
 emulsion to ultrasonic vibration.
- 2. A process according to claim 1 in which the organic compound has a Δ H/RT value in the range of 5 to 10.
 - 3. A process according to claim 1 in which the organic compound has a melting point above 20°C.
- 15 4. A process according to claim 1 in which the organic compound has a melting point between 30°C and 100°C.
 - 5. A process according to claim 1 in which the organic compound is ibuprofen, camphene, piperonal or 3-iodo-2-propynyl butyl carbamate.
 - 6. A process according to claim 1 in which the liquid dispersion medium has a crystallisation point of at least 10°C below the melting point of the organic compound and a boiling point of at least the same order as the melting point of the organic compound.
 - 7. A process according to claim 1 in which the liquid dispersion medium is an aqueous medium.
- 8. A process according to claim 1 in which the emulsion formed is an oil-in-water emulsion.

- 9. A process according to claim 1 in which the melt is added to the liquid dispersion medium while the liquid dispersion medium is at approximately the same temperature as the melt.
- 5 10. A process according to claim 1 in which the melt of the organic compound is dispersed in the liquid dispersion medium using a high shear mixer.
 - 11. A process according to claim 1 in which the melt of the organic compound is dispersed in the liquid dispersion medium using a homogeniser.
 - 12. A process according to claim 1 in which the organic compound is dispersed in the liquid dispersion medium in the form of droplets having a mean diameter of from between 1μm to 10μm.
- 13. A process according to claim 1 in which the emulsion is rapidly cooled to a temperature of from 10°C to 80°C below the melting point of the organic compound.
- 14. A process according to claim 1 in which the emulsion is subjected to ultrasonic vibration by passing a continuous stream of the emulsion through a vessel in which the ultrasonic vibration is applied.

INTERNATIONAL SEARCH REPORT

nal Application No PCT/GB 99/01432

CLASSIFICATION OF SUBJECT MATTER PC 6 B01F3/00 A61K B01D9/02 TPC 6 A61K7/00 A61K9/10 According to International Patent Classification (IPC) or to both national classification and IPC B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 6 B01F A61K B01D Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practical, search terms used) C. DOCUMENTS CONSIDERED TO BE RELEVANT Citation of document, with indication, where appropriate, of the relevant passages Relevant to claim No. Category * 1-4,7,8 EP 0 562 391 A (ROINER FRANZ ; KOHRS KLAUS Х (DE)) 29 September 1993 (1993-09-29) 9-12,14column 5, line 55 - column 6, line 53; 9 - 12WO 94 20072 A (PHARMACIA AB ; WESTESEN Υ KIRSTEN (DE); SIEKMANN BRITTA (DE)) 15 September 1994 (1994-09-15) cited in the application page 13, line 1 - page 17, line 17 14 WO 92 20420 A (ACTON ELIZABETH ; MORRIS GEORGE JOHN (GB)) 26 November 1992 (1992-11-26) page 17, line 20 - page 19, line 3; claim -/--Further documents are listed in the continuation of box C. X Patent family members are listed in annex. Х Special categories of cited documents: "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the "A" document defining the general state of the art which is not considered to be of particular relevance invention "E" earlier document but published on or after the international "X" document of particular relevance; the claimed invention filing date cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such docu-"O" document referring to an oral disclosure, use, exhibition or ments, such combination being obvious to a person skilled in the art. other means "P" document published prior to the international filing date but later than the priority date claimed "&" document member of the same patent family Date of mailing of the international search report Date of the actual completion of the international search 17/08/1999 4 August 1999 Authorized officer Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,

Fax: (+31-70) 340-3016

1

Persichini, C

INTERNATIONAL SEARCH REPORT

Inter onal Application No
PCT/GB 99/01432

	ation) DOCUMENTS CONSIDERED TO BE RELEVANT	Relevant to claim No.
Category ³	Citation of document, with indication,where appropriate, of the relevant passages	nelevant to claim No.
Р,Х	WO 98 23350 A (GEORGE NEIL ;DAWSON STEPHEN (GB); ZENECA LTD (GB); WOOD WILLIAM MA) 4 June 1998 (1998-06-04) claims	1-13
X	PATENT ABSTRACTS OF JAPAN vol. 013, no. 553 (C-663), 8 December 1989 (1989-12-08) & JP 01 228502 A (KAO CORP), 12 September 1989 (1989-09-12) abstract	1-4,7,8
Α	DE 20 57 957 A (ORSYMONDE) 27 May 1971 (1971-05-27) page 6, line 15 - page 7, line 24	1-14

1

INTERNATIONAL SEARCH REPORT

information on patent family members

Inte onal Application No PCT/GB 99/01432

Patent document cited in search report		Publication date	Patent family member(s)		Publication date	
EP 0562391	Α	29-09-1993	DE	4226850 A	30-09-1993	
WO 9420072	Α	15-09-1994	CA	2091152 A	06-09-1994	
.,			ΑU	676279 B	06-03-1997	
			AU	6225394 A	26-09-1994	
			EP	0687172 A	20-12-1995	
			FΙ	954143 A	19-10-1995	
			JP	8507515 T	13-08-1996	
			NO	953461 A	06-11-1995	
			NZ	262541 A	24-04-1997	
			US	5785976 A	28-07-1994	
			US	5885486 A	23-03-1999	
WO 9220420	A	26-11-1992	AU	1673692 A	30-12-1992	
			DE	69218194 D	17-04-1997	
			DΕ	69218194 T	02-10-1997	
			EP	05 84127 A	02-03-1994	
			JP	6509498 T	27-10-1994 	
WO 9823350	Α	04-06-1998	AU	4716997 A	22-06-1998	
JP 01228502	2 A	12-09-1989	JP	2718505 B	25-02-1998	
DE 2057957	A	27-05-1971	 FR	2068447 A	27-08-1971	
02 200,00.		_, _,	FR	2081586 A	10-12-1971	
			BE	759334 A	30-04-1971	
			CH	558659 A	14-02-1975	
			СН	528266 A	30-09-1972	
			FR	2101044 A	31-03-1972	
			GB	1328641 A	30-08-1973	
			NL	7017261 A,B,	28-05-1971	
			US	3939260 A	17-02-1976	
			BE	748897 A	16-09-1970	
			DE	2017373 A	22-04-197	
			GB	1310824 A	21-03-1973	
			US	3778510 A	11-12-1973	